

## Economy Occupational Noise Combination Kit



### Features

- One or more doseBadge Pro noise dosimeters
- Hand held CR308 sound level meter
- Protective Peli Case
- Everything for a noise survey
- All calibrated equipment

### Applications

- Smaller businesses with mobile workers
- Quick noise checks using sound level meter
- OSHA, NIOSH, ACGIH occupational noise assessments
- Detailed occupational noise assessment using doseBadges

### Overview

The Economy Combination Kit is ideal for smaller industries with a lower number of mobile workers. The CR308 is a Calibrated Type 2 Sound Level Meter and can be used for spot checks. The doseBadge Pro Noise Dosimeters are used for direct measurement of a worker's noise exposure in line with OSHA, NIOSH, ACGIH and many other regulations.

With this kit we recommend using the doseBadges for your full occupational noise survey as they provide all the measurements that are needed. The hand-held meter is a calibrated Type 2 sound level meter and is perfect for spot checks in addition to a survey carried out with the dosimeters.

For more comprehensive checks using a data logging hand-held meter, please have a look at the Integrating Combination Kit.

### Kit Contents

The Economy Combination Kit comes with the following:

- doseBadge Pro noise dosimeter(s)
- doseBadge Charger and USB Dock
- CR308 Sound Level Meter
- CR514 Sound Level Calibrator
- NoiseTools Software
- Strong, weatherproof carry case
- Calibration certificates for meter, dosimeters and calibrator

## Economy Occupational Noise Combination Kit

### Specifications

#### doseBadge Pro Noise Dosimeter Specifications

Standards	ANSI S1.25 Personal Noise Dosimeters IEC 61252 Personal Sound Exposure Meters
Range	RMS: 60 to 140 dB(A), Peak: 80 to 143 dB
Octave Bands Parameters	Real-time, 63Hz to 8kHz Date/time, Leq, Lavg, TWA, LEP,d, Lex,8, %Dose, Peak
Communication	Bluetooth to mobile app, USB to computer
Programmable	Exchange rate, criterion level & time, Threshold, Time Weighting
Logging	1 second or 1 minute time history (user selectable)
Dimensions	2.54" x 1.69" x 2.01" x 66 x 43 x 53mm

For more detailed specifications please visit the doseBadge Pro Noise Dosimeter page.

#### CR308 Sound Level Meter Specifications

Standards	ANSI S1.4 Type 2 IEC 61672 Class 2
Range	30 to 130 dB(A), 40 to 130 dB(C)
Freq. Weighting	A and C
Time Weighting	Fast and Slow
Functions	Sound level, max, min, Peak
Flags	Alarm limit, overload, under-range
Resolution	0.1 dB
Power	2 x AA / LR6 1.5V batteries

For more detailed specifications please visit the CR308 Sound Level Meter page.

---

#### Head Office

NoiseMeters Inc  
3233 Coolidge Hwy  
Berkley  
MI 48072  
USA

Telephone **888 206 4377**  
Fax **888 584 2230**

Email: [info@noisemeters.com](mailto:info@noisemeters.com)  
Support: [support@noisemeters.com](mailto:support@noisemeters.com)

#### Web Sites

Main site:  
<https://www.noisemeters.com>

Product shortcut:  
<https://www.noisemeters.com/p/cmb308/1/>

Tech Support:  
<https://support.noisemeters.com>